









LEGEND

	UNPAID AREA
	PAID AREA
	BACK OF HOUSE AREA
	PUBLIC DOMAIN
	OPERATIONAL AREA
	TOILET & UTILITIES
	RCC

<u>DRG.NO.</u> KRIDE / BSRP / C2 / TD / MAT / AR / 1000				
<u>DRG ISSUE DATE</u>	<u>REVISION NO.</u>	<u>DRAWN BY</u>	<u>CHKD BY</u>	<u>APRVD BY</u>
11 / 06 / 2024	01	VSA	VSA	----



-	Scale (A1) 1:300, (A3) 1:600
---	------------------------------

ROOM AREA SCHEDULE				
S.NO	ROOM NAME	WIDTH	LENGTH	AREA
1	SCR	10856	5000	60 SQM
2	SER / TER	12516	4200	50 SQM
3	UPS (S&T)	12510	4040	50 SQM
4	STATION UPS	5300	8683	45 SQM
5	ASS ROOM	10000	20160	201 SQM
6	TOM - 1&2	2100	2100	4 SQM
7	EFO - 1&2	1865	2100	4 sqm
8	CLEANER'S / REFUSE ROOM	2000	4233	8 sqm
9	STAFF ROOM	3100	5916	18 sqm
10	SECURITY ROOM-1	1500	1725	2.5 SQM
11	SECURITY ROOM-2	2270	3560	8 SQM

ROOM AREA SCHEDULE				
S.NO	ROOM NAME	WIDTH	LENGTH	AREA
12	TOILET (M) -1	3170	4040	13 SQM
13	TOILET (F) -1	5090	2140	10 SQM
14	TOILET (H) -1	2330	2140	10 SQM
15	LACTATION -1	2400	2400	6 SQM
16	TOILET (M) -2	3000	3215	11 SQM
17	TOILET (F) -2	3500	2915	10 SQM
18	TOILET (H) -2	2100	2400	5 SQM
19	LACTATION -2	2200	2100	5 SQM
20	FIRE WATER TANK (1 NOS) 100 KL CAPACITY	5450	6000	100 KL.Cap
21	DOMESTIC WATER TANK (2 NOS) 50 KL CAPACITY	12610	2215	50 KL.Cap
22				








OPENING SCHEDULE						
OPENING TYPE	WIDTH	HEIGHT	LINTEL HEIGHT	SILL HEIGHT	Nos.	REMARKS
D1	1000	2100	2150	---	14	SINGLE LEAF DOOR
SD	1200	2100	2150	---	02	SLIDING DOOR
GD	1000	2100	2150	---	04	GLASS DOOR
FD1	2100	2400	2450	---	06	FIRE RATED DOOR
RS1	3000	3500	3500	---	05	ROLLING SHUTTER
RS2	4000	3500	3500	---	03	ROLLING SHUTTER
RS3	6000	3500	3500	---	02	ROLLING SHUTTER

ABBREVIATIONS	FULL FORM
F.F.L	Floor Finish Level
TOM	Ticket Operating Machine
SCR	Station Control Room
EFO	Ecess Fare Office
SER	Signaling Equipment Room
TER	Telecom Equipment Room
UPS	Uninterruptible Power Supply
S&T	Signaling & Telecom
ASS	Auxiliary sub station
MMI	Multi Modal Integration

* HEIGHTS AND LEVELS MARKED ARE INDICATIVE ONLY

* HEIGHTS AND LEVELS ARE SUBJECT TO CHANGE AS PER EXISTING SITE CONDITIONS



LEGEND

	UNPAID AREA
	PAID AREA
	BACK OF HOUSE AREA
	PUBLIC DOMAIN
	OPERATIONAL AREA
	TOILET & UTILITIES
	RCC

NOTES:

1. ALL DIMENSIONS ARE TENTATIVE FOR ILLUSTRATION PURPOSE, BOQ CONTRACTOR WILL DO ACTUAL DESIGN AS PER SITE CONDITION, SPACE AVAILABLE, CONSTRUCTION FEASIBILITY ETC.
2. ALL DIMENSIONS ARE IN MILLIMETERS.
3. ALL DIMENSIONS ARE TO BE READ AND NOT TO MEASURED.
4. ROOF SHOULD BE DESIGNED FOR INSTALLATION OF SOLAR PANELS, ROOF SHAPE AND SIZE IS INDICATIVE. CONTRACTOR TO PROVIDE OPTIONS SUFFICIENTLY DETAILED FOR EMPLOYERS APPROVAL. FOR FURTHER DETAIL PLEASE REFER THE EMPLOYERS REQUIREMENT.
5. CONTRACTOR TO DESIGN A AESTHETICALLY PLEASING , STATE OF THE ART FACADE SYSTEM TO STOP INGRESS OF WATER IN THE STATION. ANY STRUCTURAL LOAD ON ACCOUNT OF THE FACADE WILL BE TAKEN CARE BY THE CONTRACTOR IN THEIR STRUCTURAL DESIGN
6. BARE SHELL IS WITHOUT ANY ARCHITECTURAL FINISHES AND E&M PROVISIONS.
7. ALL FOB SUPPORT LOCATIONS ARE INDICATIVE CONTRACTOR TO CO-ORDINATE WITH CONCERNED AUTHORITIES AND FINALIZE THE LOCATION AS PER ACTUAL SITE CONDITION ENSURING ALL NECESSARY CLEARANCES.
8. THE CUTOFF FOR FUTURE ESC./STAIRCASE SHALL BE CONSTRUCTED AS PRESENT SCHEME AND SHALL BE COVERED WITH A TEMPORARY SLAB FOR USE AS PUBLIC DOMAIN SPACE.


K-RIDE			K-RIDE GC
			Project Director GC
			Architect GC



Drawing for Tender Purpose only

RG.NO.
RIDE / BSRP / C2 / TD / MAT / AR / 1001

<u>DRG.NO.</u> KRIDE / BSRP / C2 / TD / MAT / AR / 1001				
<u>DRG ISSUE DATE</u> 11 / 06 / 2024	<u>REVISION NO.</u> 01	<u>DRAWN BY</u> VSA	<u>CHKD BY</u> VSA	<u>APRVD BY</u> -----



1	MID LEVEL - 2
-	Scale (A1) 1:300, (A3) 1:600

ROOM AREA SCHEDULE				
S.NO	ROOM NAME	WIDTH	LENGTH	AREA
1	SCR	10856	5000	60 SQM
2	SER / TER	12516	4200	50 SQM
3	UPS (S&T)	12510	4040	50 SQM
4	STATION UPS	5300	8683	45 SQM
5	ASS ROOM	10000	20160	201 SQM
6	TOM - 1&2	2100	2100	4 SQM
7	EFO - 1&2	1865	2100	4 sqm
8	CLEANER'S / REFUSE ROOM	2000	4233	8 sqm
9	STAFF ROOM	3100	5916	18 sqm
10	SECURITY ROOM-1	1500	1725	2.5 SQM
11	SECURITY ROOM-2	2270	3560	8 SQM

ROOM AREA SCHEDULE				
S.NO	ROOM NAME	WIDTH	LENGTH	AREA
12	TOILET (M) -1	3170	4040	13 SQM
13	TOILET (F) -1	5090	2140	10 SQM
14	TOILET (H) -1	2330	2140	10 SQM
15	LACTATION -1	2400	2400	6 SQM
16	TOILET (M) -2	3000	3215	11 SQM
17	TOILET (F) -2	3500	2915	10 SQM
18	TOILET (H) -2	2100	2400	5 SQM
19	LACTATION -2	2200	2100	5 SQM
20	FIRE WATER TANK (1 NOS) 100 KL CAPACITY	5450	6000	100 KL.Cap
21	DOMESTIC WATER TANK (2 NOS) 50 KL CAPACITY	12610	2215	50 KL.Cap
22				








OPENING SCHEDULE						
OPENING TYPE	WIDTH	HEIGHT	LINTEL HEIGHT	SILL HEIGHT	Nos.	REMARKS
D1	1000	2100	2150	---	14	SINGLE LEAF DOOR
SD	1200	2100	2150	---	02	SLIDING DOOR
GD	1000	2100	2150	---	04	GLASS DOOR
FD1	2100	2400	2450	---	06	FIRE RATED DOOR
RS1	3000	3500	3500	---	05	ROLLING SHUTTER
RS2	4000	3500	3500	---	03	ROLLING SHUTTER
RS3	6000	3500	3500	---	02	ROLLING SHUTTER

ABBREVIATIONS	FULL FORM
F.F.L	Floor Finish Level
TOM	Ticket Operating Machine
SCR	Station Control Room
EFO	Eccess Fare Office
SER	Signaling Equipment Room
TER	Telecom Equipment Room
UPS	Uninterruptible Power Supply
S&T	Signaling & Telecom
ASS	Auxiliary sub station
MMI	Multi Modal Integration

NOTE :

- * HEIGHTS AND LEVELS MARKED ARE INDICATIVE ONLY
- * HEIGHTS AND LEVELS ARE SUBJECT TO CHANGE AS PER EXISTING SITE CONDITIONS



LEGEND

	UNPAID AREA
	PAID AREA
	BACK OF HOUSE AREA
	PUBLIC DOMAIN
	OPERATIONAL AREA
	TOILET & UTILITIES
	RCC


NOTES:

1. ALL DIMENSIONS ARE TENTATIVE FOR ILLUSTRATION PURPOSE, BOQ CONTRACTOR WILL DO ACTUAL DESIGN AS PER SITE CONDITION, SPACE AVAILABLE, CONSTRUCTION FEASIBILITY ETC.
2. ALL DIMENSIONS ARE IN MILLIMETERS.
3. ALL DIMENSIONS ARE TO BE READ AND NOT TO MEASURED.
4. ROOF SHOULD BE DESIGNED FOR INSTALLATION OF SOLAR PANELS, ROOF SHAPE AND SIZE IS INDICATIVE. CONTRACTOR TO PROVIDE OPTIONS SUFFICIENTLY DETAILED FOR EMPLOYERS APPROVAL. FOR FURTHER DETAIL PLEASE REFER THE EMPLOYERS REQUIREMENT.
5. CONTRACTOR TO DESIGN A AESTHETICALLY PLEASING , STATE OF THE ART FACADE SYSTEM TO STOP INGRESS OF WATER IN THE STATION. ANY STRUCTURAL LOAD ON ACCOUNT OF THE FACADE WILL BE TAKEN CARE BY THE CONTRACTOR IN THEIR STRUCTURAL DESIGN
6. BARE SHELL IS WITHOUT ANY ARCHITECTURAL FINISHES AND E&M PROVISIONS.
7. ALL FOB SUPPORT LOCATIONS ARE INDICATIVE CONTRACTOR TO CO-ORDINATE WITH CONCERNED AUTHORITIES AND FINALIZE THE LOCATION AS PER ACTUAL SITE CONDITION ENSURING ALL NECESSARY CLEARANCES.
8. THE CUTOFF FOR FUTURE ESC./STAIRCASE SHALL BE CONSTRUCTED AS PRESENT SCHEME AND SHALL BE COVERED WITH A TEMPORARY SLAB FOR USE AS PUBLIC DOMAIN SPACE.

K-RIDE			K-RIDE GC
			Project Director GC
			Architect GC



BANGALORE SUB URBAN RAIL PROJECT CORRIDOR - 2			
Drawing for Tender Purpose only			
MATHIKERE MID LEVEL-2 PLAN			
DRG.NO. KRIDE / BSRP / C2 / TD / MAT / AR / 1002			
DRG ISSUE DATE 11 / 06 / 2024	REVISION NO. 01	DRAWN BY VSA	CHKD BY VSA
		APRVD BY -----	










ROOM AREA SCHEDULE				
S.NO	ROOM NAME	WIDTH	LENGTH	AREA
12	TOILET (M) -1	3170	4040	13 SQM
13	TOILET (F) -1	5090	2140	10 SQM
14	TOILET (H) -1	2330	2140	10 SQM
15	LACTATION -1	2400	2400	6 SQM
16	TOILET (M) -2	3000	3215	11 SQM
17	TOILET (F) -2	3500	2915	10 SQM
18	TOILET (H) -2	2100	2400	5 SQM
19	LACTATION -2	2200	2100	5 SQM
20	FIRE WATER TANK (1 NOS) 100 KL CAPACITY	5450	6000	100 KL.Cap
21	DOMESTIC WATER TANK (2 NOS) 50 KL CAPACITY	12610	2215	50 KL.Cap
22				


ABBREVIATIONS	FULL FORM
F.F.L	Floor Finish Level
TOM	Ticket Operating Machine
SCR	Station Control Room
EFO	Ecess Fare Office
SER	Signaling Equipment Room
TER	Telecom Equipment Room
UPS	Uninterruptible Power Supply
S&T	Signaling & Telecom
ASS	Auxiliary sub station
MMI	Multi Modal Integration

* HEIGHTS AND LEVELS MARKED ARE INDICATIVE ONLY

* HEIGHTS AND LEVELS ARE SUBJECT TO CHANGE AS PER EXISTING SITE CONDITIONS

LEGEND	
	UNPAID AREA
	PAID AREA
	BACK OF HOUSE AREA
	PUBLIC DOMAIN
	OPERATIONAL AREA
	TOILET & UTILITIES
	RCC

K-RIDE			K-RIDE GC
			Project Director GC
			Architect GC _____




Drawing for Tender Purpose only


MATHIKERE PLATFORM LEVEL PLAN

DRG.NO.
KPIB / BOPB / 00 / TD / MAT / AB / 1000

<u>DRG ISSUE DATE</u>	<u>REVISION NO.</u>	<u>DRAWN BY</u>	<u>CHKD BY</u>	<u>APRVD BY</u>
11 / 06 / 2024	01	VSA	VSA	*****



1 | **EE-1 CROSS SECTION - A**
- | Scale (A1) 1:150, (A3) 1:300



2 | **EE-2 CROSS SECTION - B**
- | Scale (A1) 1:150, (A3) 1:300

ROOM AREA SCHEDULE				
S.NO	ROOM NAME	WIDTH	LENGTH	AREA
1	SCR	10856	5000	60 SQM
2	SER / TER	12516	4200	50 SQM
3	UPS (S&T)	12510	4040	50 SQM
4	STATION UPS	5300	8683	45 SQM
5	ASS ROOM	10000	20160	201 SQM
6	TOM - 1&2	2100	2100	4 SQM
7	EFO - 1&2	1865	2100	4 sqm
8	CLEANER'S / REFUSE ROOM	2000	4233	8 sqm
9	STAFF ROOM	3100	5916	18 sqm
10	SECURITY ROOM-1	1500	1725	2.5 SQM
11	SECURITY ROOM-2	2270	3560	8 SQM

ROOM AREA SCHEDULE				
S.NO	ROOM NAME	WIDTH	LENGTH	AREA
12	TOILET (M) -1	3170	4040	13 SQM
13	TOILET (F) -1	5090	2140	10 SQM
14	TOILET (H) -1	2330	2140	10 SQM
15	LACTATION -1	2400	2400	6 SQM
16	TOILET (M) -2	3000	3215	11 SQM
17	TOILET (F) -2	3500	2915	10 SQM
18	TOILET (H) -2	2100	2400	5 SQM
19	LACTATION -2	2200	2100	5 SQM
20	FIRE WATER TANK (1 NOS) 100 KL CAPACITY	5450	6000	100 KL.Cap
21	DOMESTIC WATER TANK (2 NOS) 50 KL CAPACITY	12610	2215	50 KL.Cap
22				

OPENING SCHEDULE						
OPENING TYPE	WIDTH	HEIGHT	LINTEL HEIGHT	SILL HEIGHT	Nos.	REMARKS
D1	1000	2100	2150	---	14	SINGLE LEAF DOOR
SD	1200	2100	2150	---	02	SLIDING DOOR
GD	1000	2100	2150	---	04	GLASS DOOR
FD1	2100	2400	2450	---	06	FIRE RATED DOOR
RS1	3000	3500	3500	---	05	ROLLING SHUTTER
RS2	4000	3500	3500	---	03	ROLLING SHUTTER
RS3	6000	3500	3500	---	02	ROLLING SHUTTER



ABBREVIATIONS	FULL FORM
F.F.L	Floor Finish Level
TOM	Ticket Operating Machine
SCR	Station Control Room
EFO	Eccess Fare Office
SER	Signaling Equipment Room
TER	Telecom Equipment Room
UPS	Uninterruptible Power Supply
S&T	Signaling & Telecom
ASS	Auxiliary sub station
MMI	Multi Modal Integration

NOTE :
* HEIGHTS AND LEVELS MARKED ARE INDICATIVE ONLY
* HEIGHTS AND LEVELS ARE SUBJECT TO CHANGE AS PER EXISTING SITE CONDITIONS

LEGEND	
	UNPAID AREA
	PAID AREA
	BACK OF HOUSE AREA
	PUBLIC DOMAIN
	OPERATIONAL AREA
	TOILET & UTILITIES
	RCC

NOTES:
1. ALL DIMENSIONS ARE TENTATIVE FOR ILLUSTRATION PURPOSE, BOQ CONTRACTOR WILL DO ACTUAL DESIGN AS PER SITE CONDITION, SPACE AVAILABLE, CONSTRUCTION FEASIBILITY ETC..
2. ALL DIMENSIONS ARE IN MILLIMETERS.
3. ALL DIMENSIONS ARE TO BE READ AND NOT TO MEASURED.
4. ROOF SHOULD BE DESIGNED FOR INSTALLATION OF SOLAR PANELS, ROOF SHAPE AND SIZE IS INDICATIVE. CONTRACTOR TO PROVIDE OPTIONS SUFFICIENTLY DETAILED FOR EMPLOYERS APPROVAL. FOR FURTHER DETAIL PLEASE REFER THE EMPLOYERS REQUIREMENT.
5. CONTRACTOR TO DESIGN A AESTHETICALLY PLEASING , STATE OF THE ART FACADE SYSTEM TO STOP INGRESS OF WATER IN THE STATION. ANY STRUCTURAL LOAD ON ACCOUNT OF THE FACADE WILL BE TAKEN CARE BY THE CONTRACTOR IN THEIR STRUCTURAL DESIGN
6. BARE SHELL IS WITHOUT ANY ARCHITECTURAL FINISHES AND E&M PROVISIONS.
7. ALL FOB SUPPORT LOCATIONS ARE INDICATIVE CONTRACTOR TO CO-ORDINATE WITH CONCERNED AUTHORITIES AND FINALIZE THE LOCATION AS PER ACTUAL SITE CONDITION ENSURING ALL NECESSARY CLEARANCES.
8. THE CUTOUT FOR FUTURE ESC./STAIRCASE SHALL BE CONSTRUCTED AS PRESENT SCHEME AND SHALL BE COVERED WITH A TEMPORARY SLAB FOR USE AS PUBLIC DOMAIN SPACE.

K-RIDE			K-RIDE GC		
			Project Director GC		
			Architect GC		



BANGALORE SUB URBAN RAIL PROJECT
CORRIDOR - 2

Drawing for Tender Purpose only

**MATHIKERE
EE- 1 & 2 CROSS SECTIONS**

DRG.NO.
KRIDE / BSRP / C2 / TD / MAT / AR / 1005

DRG ISSUE DATE
11 / 06 / 2024

REVISION NO.
01

DRAWN BY
VSA

CHKD BY
VSA

APRVD BY

ARCHITECTURAL