




SAME PATTERN TO BE USED FOR  
EXPOSED PART OF RETAINING WALL  
WITHIN SITE



FOUNDING LEVEL SHALL BE MINIMUM 1200 BELOW  
NATURAL GROUND LEVEL  
TOP OF PLINTH BEAM SHALL BE 20MM ABOVE TH  
FORMATION LEVEL /OUTSIDE GROUND LEVEL



11. 1 IN 8.5 TURNOUTS PROVIDED IN THE DEPOT.

12. FM DISTANCE PROVIDED AT 4.25M METERS.

R0	TENDER DRAWING	DAMODARA REDDY (AGP)	VENKATESH (SVH)	UMMA PRASAD (KLP)	GOPALA REDDY (VGR)
		AGP 28/08/2024	SVH 28/08/2024	KLP 28/08/2024	VGR 28/08/2024
REV NO.	DESCRIPTION	DESIGNED	CHECKED	REVIEWED	APPROVED

CHIEF TRACTION EXPERT		SWT SIGNALLING	
CHIEF TELECOM EXPERT			
SR.ROLLING STOCK ENGINEER			

DIRECTOR PROJECT PLANNING	DIRECTOR SYSTEM
------------------------------	-----------------

SCALE 1:75	SHEET NO. 1 OF 2	DRG NO. KRIDE_BSRP_RS_DEPOT_SDVL	REV 05
---------------	---------------------	----------------------------------	-----------