BENNIGANAHALLI
DN LINE
UP LINE
EXG. LOTTEGOLLAHALLI (LOGH) CROSSING STATION CH AT EXG. LINE: 220/000 AT BSRP CH: 14+310
CL OF MATHIKERE STATION (SUBURBAN ELEVATED PF'S & STATION) AT CH: 15669
TENTATIVE LOCATION OF DA SHOWN, OHE TO BE SUPPORTED FROM TRUSSES AND DISTANCE OF TRUSSES REQUIRED FROM STATION BUILDING CONTRACTOR.
PROPOSED SUBURBAN PLATFORM
UIOL FOR DN LINE
UIOL FOR UP LINE
IOL FOR DN LINE
IOL FOR UP LINE
FP MATHIKERE CH: 14.980Km (approx.)
SS MATHIKERE CH: 16.506 KM
ACC CENTRE FOR DN MAIN
ACC CENTRE FOR UP MAIN
# Reffer Note 7
CHIKKABANAVARA
YESVANTPUR
14+200
14+300
14+400
14+500
14+600
14+700
14+800
14+900
15+000
15+100
15+200
15+300
15+400
15+500
15+600
15+700
15+800
15+900
16+000
16+100
16+200
16+300
16+400
16+500
16+600
16+700
17+000

BENNIGANAHALLI
SOLADEVANAHALLI
KM17
SS MATHIKERE
FUTURE STN. SUBURBAN
DN LINE
UP LINE
YESVANTPUR SUBURBAN
MATHIKERE SUBURBAN
FP MATHIKERE CH: 14.98KM
SS MATHIKERE CH: 16.506 KM

LEGEND

Sr. No.	DESCRIPTION	SYMBOL
1	OHE Span length in metres	(30)
2	Insulated Overlap (IOL)	
3	Un insulated Overlap (UIOL)	
4	Section Insulator	
5	Single Pole Isolator	
6	Double pole Isolator with Earth Heel	
7	Normal Mast with Single Cantilever Assembly at Viaduct	
8	Normal Mast with Multiple Cantilever Assembly at Viaduct	
9	Normal Mast with triple Cantilever Assembly at Viaduct	
10	Portal with Drop Arm and Single Cantilever Assembly at Viaduct	
11	Portal with Drop Arm and Double Cantilever Assembly at Viaduct	
12	Two Track Cantilever Assembly (TTC 5.50/8.0) at Viaduct	
13	Normal Mast with Single Cantilever Assembly at Grade	
14	Normal Mast with Multiple Cantilever Assembly at Grade	
15	Normal Mast with triple Cantilever Assembly at Grade	
16	Portal with Drop Arm and Single Cantilever Assembly at Grade	
17	Portal with Drop Arm and Double Cantilever Assembly at Grade	
18	Two Track Cantilever Assembly (TTC 5.50/8.0) at Grade	
19	Drop arm support with single cantilever (6"x6" DA)	
20	Drop arm support with Double cantilever (8"x6" DA)	
21	Drop arm support with triple cantilever (8"x6" DA)	
22	Anchoring stay with Fixed Termination-conv.	FTA
23	Anchoring Stay with Spring Termination Anchor	BWA
24	Versine	300
25	Anticreep Anchor	ACA
26	Anticreep Center	ACC
27	Tension Length	TL
28	Upright Details (Clearspan)	BFBU/GU(CS:xx)
29	Sub-Sectioning and Paralleling Post (SSP)	
30	Sub-Sectioning Post (SS)	
31	Sectioning and Paralleling Post (SP)	
32	Feeding Post (FP)	
33	Obligatory	OBL
34	To Be Decided	TBD
35	Interrupter(BM)	
36	Potential Transformer (PT)	
37	Lightning Arrestor (LA)	
38	Booster Transformer	
39	Spare	
40	Overhead Protection Conductor Anchor	OPCA
41	Return Conductor Anchor	RCA
42	Tramway OHE	
43	In-Run Wire	
44	Out-of Run Wire	
45	PTFE	
46	Overhead Protection Conductor	OPC
47	Return Conductor	RC
48	Cross feeder	
49	Slack feeder	
50	Full Feeding Jumper	
51	Potential Equalising Jumper	
52	In-Span Jumper	
53	RC and OPC Support	
54	Track at Lower level (Corridor 2)	
55	Track at UP/DN line (Corridor 2)	
56	Track at UP & DN (Corridor 1)	

NOTES:-

1. ALL DIMENSIONS ARE IN METERS UNLESS NOTED OTHERWISE.
2. ALL DIMENSIONS ARE TO BE READ AND NOT TO BE MEASURED.
3. ALIGNMENT OF THE PEGGING PLAN HAS BEEN PREPARED ACCORDING TO THE ALIGNMENT DRAWING RECEIVED FROM GC / KRIDE DT. 08-07-2024.
4. OHE CHAINAGE OF PEGGING PLAN HAS BEEN REFERRED ACCORDING TO THE ELEVATED GAD RECEIVED FROM L&T ON 10-07-2024:
   - FOR UP & DN (P-96 TO P-181-10) REFER TO "DRG NO. O22077-BSRP-CR2-C-VD-GEN-10-2007-2010."
   - FOR UP LINE (P 181-11 TO UP 192) REFER TO "DRG NO. O22077-BSRP-CR2-C-VD-GEN-20-2064."
   - FOR DN LINE (P181-11 TO DP192) REFER TO "DRG NO. O22077-BSRP-CR2-C-VD-GEN-20-2061."
5. CHAINAGES OF OHE LOCATION HAS BEEN CONSIDERED WITH RESPECT TO PIER CENTER LINE DESIGN CHAINAGE FOR BOTH UP & DN LINE UPTO LOCATION NO. 16/31 & 16/32.
6. LOCATION NO. 16/33 & 16/34 ONWARDS DIFFERENT CHAINAGE FOR UP & DN LINE TO BE FOLLOWED AS MENTIONED IN REVISED HDB LIST, DOCUMENT NO. KRDD01-PRD-CR02-GEN-OCS-HDB-00002. DT. 01-08-2024
8. SPANS ARE ROUNDED OFF TO NEAREST SINGLE DECIMAL.
9. MAST TYPE SHALL BE DEMARCATED IN PEGGING PLAN AFTER FINALIZATION OF OHE LOAD CALCULATIONS.
10. FOR UP LINE IN THE INCREASING ORDER OF THE PIER NO FROM UP186 TO PP193 PEDESTAL ON THE LEFT SIDE OF THE GIRDER TO BE STRENGTHEN FOR OHE LOCATION.
11. OHE HEIGHT CLEARANCE UNDER/OVER LINE STRUCTURE (HT. LINE X-ING ETC.) TO BE CONFIRMED OR SPECIAL CARE TO BE TAKEN BEFORE ERECTION FOR THAT PARTICULAR AREA WHEREVER REQUIRED.

FOR TENDER PURPOSE ONLY

NOTES:
1. ALL DIMENSIONS ARE IN METER UNLESS MENTIONED OTHERWISE.
2. ALL DIMENSIONS ARE TO BE READ AND NOT TO BE MEASURED.
3. ANY DISCREPANCY IN THE DRAWING MUST BE BROUGHT TO THE NOTICE OF THE DESIGNER.
4. INTERFACE WITH OTHER DESIGN DISCIPLINE WILL BE DONE AS PER AVAILABILITY OF DETAILS.

REV	DATE	DESCRIPTION	Originator	Checked	Approved
R0	14-08-2024	First Submission	IA / SB	CK/NP	RK/SK

K RIDE

DM / ELE / KRIDE	Sr. DGM / ELE / KRIDE	AGM / ELE / KRIDE

Certified that this document has been designed and checked in accordance with GC Quality Assurance Plan.

EGIS-AECOM-WSP

Senior Discipline Expert	Chief Discipline Expert	Project Director

Certified that this document has been designed and checked in accordance with DDC Quality Assurance Plan.

Detailed Design Consultant for design of Traction & Auxiliary Power Supply and Distribution for BSRP

SYSTRA MVA CONSULTING (INDIA) PVT. LTD.
10th and 11th Floor, Tower-B, 12/3, Vatika Mindscapes, Mathura Road, NH2, Sector 27D, Faridabad, Haryana 121013

Drawn	Checked:	Approved:
I. Alam	D. Kalyan	R. Kapoor
S. Bhati	N. Parmar	S. Kumar

Client:
RAIL INFRASTRUCTURE DEVELOPMENT COMPANY (KARNATAKA) LIMITED

Project Title: Bengaluru Suburban Rail Project (BSRP)
(Detailed Design Consultant for design of Traction & Auxiliary Power Supply and Distribution for BSRP)

Corridor-2 (Benniganahalli -Soladevanahalli)

Drawing Title: OHE Pegging Plan for Main Line CH: 014+062.903(P96)Km to CH:16+854.784/16+855.916Km (UP192/DP192)

Project Stage: Tender Drawing

Paper Size: A3
Discipline: Power Supply & Traction System
Date: 14/08/2024
Scale: NTS
Drawing no.: KRDD01-TDR-CR02-GEN-OCS-PGP-00007
Revision: R0