
ELECTRICAL SUBSTATION
CHINDA BARGAON SUBSTATION
KEY PLAN
TRACTION LOCATIONS OF OHE MAST, OHE TUBE SUPPORTED FROM TRUSSES
TRACTION LOCATIONS OF OHE MAST, OHE TUBE SUPPORTED FROM BRIDGE
GENERAL NOTES
1. ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED.
2. ALL LEVELS ARE IN METERS.
3. THE CONTRACTOR SHALL VERIFY ALL DIMENSIONS AT SITE BEFORE FABRICATION.
4. ANY DISCREPANCY IN DRAWINGS SHALL BE REPORTED TO THE ENGINEER.
5. THE CONTRACTOR SHALL ENSURE ALL WORKS COMPLY WITH RELEVANT STANDARDS.
6. ALL STRUCTURES SHALL BE PROTECTED AGAINST CORROSION.
7. THE CONTRACTOR SHALL PROVIDE AS-BUILT DRAWINGS UPON COMPLETION.
8. ALL WELDING SHALL BE PERFORMED BY CERTIFIED WELDERS.
9. THE CONTRACTOR SHALL OBTAIN ALL NECESSARY PERMITS BEFORE COMMENCING WORK.
10. ALL MATERIALS SHALL BE NEW AND OF APPROVED QUALITY.
11. THE CONTRACTOR SHALL MAINTAIN A SAFE WORKING ENVIRONMENT AT ALL TIMES.
12. ALL DRAWINGS ARE TO BE READ IN CONJUNCTION WITH RELEVANT SPECIFICATIONS.
13. THE CONTRACTOR SHALL ENSURE ADEQUATE TRAFFIC MANAGEMENT DURING CONSTRUCTION.
14. ALL DISTANCES ARE MEASURED ALONG THE CENTRE LINE OF THE TRACK UNLESS NOTED.
15. THE CONTRACTOR SHALL PROVIDE ADEQUATE LIGHTING FOR NIGHT WORKS.
16. ALL EXCAVATED MATERIAL SHALL BE DISPOSED OF AS DIRECTED BY THE ENGINEER.
17. THE CONTRACTOR SHALL ENSURE ADEQUATE DRAINAGE AT ALL WORK SITES.
18. ALL CONCRETE SHALL BE OF GRADE M30 UNLESS OTHERWISE SPECIFIED.
19. THE CONTRACTOR SHALL PROVIDE TEMPORARY SUPPORTS WHERE REQUIRED.
20. ALL REINFORCEMENT SHALL BE FREE FROM RUST AND LOOSE SCALE.
21. THE CONTRACTOR SHALL NOTIFY THE ENGINEER 48 HOURS BEFORE CONCRETE POURING.
22. ALL CABLE ROUTES SHALL BE MARKED ON SITE BEFORE EXCAVATION.
23. THE CONTRACTOR SHALL ENSURE ADEQUATE EARTHING FOR ALL METALLIC STRUCTURES.
24. ALL CABLES SHALL BE TESTED BEFORE AND AFTER INSTALLATION.
25. THE CONTRACTOR SHALL PROVIDE CABLE IDENTIFICATION TAGS AT ALL JUNCTIONS.
26. ALL CABLE TRENCHES SHALL BE BACKFILLED WITH APPROVED MATERIAL ONLY.
27. THE CONTRACTOR SHALL ENSURE ADEQUATE COMPACTION OF BACKFILL MATERIAL.
28. ALL CABLE JOINTS SHALL BE MADE BY CERTIFIED JOINTERS ONLY.
29. THE CONTRACTOR SHALL PROVIDE CABLE PROTECTION WHERE CABLES CROSS ROADS.
30. ALL CABLE DRUMS SHALL BE HANDLED WITH CARE TO AVOID DAMAGE.
31. THE CONTRACTOR SHALL ENSURE ADEQUATE VENTILATION IN CABLE TUNNELS.
32. ALL CABLE SUPPORTS SHALL BE SPACED AT INTERVALS NOT EXCEEDING 1.5 METERS.
33. THE CONTRACTOR SHALL PROVIDE FIRE STOPPING AT ALL CABLE PENETRATIONS.
34. ALL CABLE GLANDS SHALL BE OF APPROVED TYPE AND SIZE.
35. THE CONTRACTOR SHALL ENSURE ADEQUATE SEPARATION BETWEEN POWER AND CONTROL CABLES.
36. ALL CABLE TERMINATIONS SHALL BE MADE IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.
37. THE CONTRACTOR SHALL PROVIDE CABLE SCHEDULES UPON COMPLETION.
38. ALL CABLE ROUTES SHALL BE APPROVED BY THE ENGINEER BEFORE INSTALLATION.
39. THE CONTRACTOR SHALL ENSURE ADEQUATE CLEARANCE FROM OTHER UTILITIES.
40. ALL CABLE TRENCHES SHALL BE MARKED WITH WARNING TAPE.
41. THE CONTRACTOR SHALL PROVIDE CABLE DRUM TURNING GEAR.
42. ALL CABLE PULLING SHALL BE DONE UNDER SUPERVISION.
43. THE CONTRACTOR SHALL ENSURE ADEQUATE LIGHTING IN CABLE TUNNELS.
44. ALL CABLE SUPPORTS SHALL BE GALVANIZED.
45. THE CONTRACTOR SHALL PROVIDE CABLE IDENTIFICATION TAGS AT ALL JUNCTIONS.
46. ALL CABLE TRENCHES SHALL BE BACKFILLED WITH APPROVED MATERIAL ONLY.
47. THE CONTRACTOR SHALL ENSURE ADEQUATE COMPACTION OF BACKFILL MATERIAL.
48. ALL CABLE JOINTS SHALL BE MADE BY CERTIFIED JOINTERS ONLY.
49. THE CONTRACTOR SHALL PROVIDE CABLE PROTECTION WHERE CABLES CROSS ROADS.
50. ALL CABLE DRUMS SHALL BE HANDLED WITH CARE TO AVOID DAMAGE.
51. THE CONTRACTOR SHALL ENSURE ADEQUATE VENTILATION IN CABLE TUNNELS.
52. ALL CABLE SUPPORTS SHALL BE SPACED AT INTERVALS NOT EXCEEDING 1.5 METERS.
53. THE CONTRACTOR SHALL PROVIDE FIRE STOPPING AT ALL CABLE PENETRATIONS.
54. ALL CABLE GLANDS SHALL BE OF APPROVED TYPE AND SIZE.
55. THE CONTRACTOR SHALL ENSURE ADEQUATE SEPARATION BETWEEN POWER AND CONTROL CABLES.
56. ALL CABLE TERMINATIONS SHALL BE MADE IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.
57. THE CONTRACTOR SHALL PROVIDE CABLE SCHEDULES UPON COMPLETION.
58. ALL CABLE ROUTES SHALL BE APPROVED BY THE ENGINEER BEFORE INSTALLATION.
59. THE CONTRACTOR SHALL ENSURE ADEQUATE CLEARANCE FROM OTHER UTILITIES.
60. ALL CABLE TRENCHES SHALL BE MARKED WITH WARNING TAPE.
61. THE CONTRACTOR SHALL PROVIDE CABLE DRUM TURNING GEAR.
62. ALL CABLE PULLING SHALL BE DONE UNDER SUPERVISION.
63. THE CONTRACTOR SHALL ENSURE ADEQUATE LIGHTING IN CABLE TUNNELS.
64. ALL CABLE SUPPORTS SHALL BE GALVANIZED.
65. THE CONTRACTOR SHALL PROVIDE CABLE IDENTIFICATION TAGS AT ALL JUNCTIONS.
66. ALL CABLE TRENCHES SHALL BE BACKFILLED WITH APPROVED MATERIAL ONLY.
67. THE CONTRACTOR SHALL ENSURE ADEQUATE COMPACTION OF BACKFILL MATERIAL.
68. ALL CABLE JOINTS SHALL BE MADE BY CERTIFIED JOINTERS ONLY.
69. THE CONTRACTOR SHALL PROVIDE CABLE PROTECTION WHERE CABLES CROSS ROADS.
70. ALL CABLE DRUMS SHALL BE HANDLED WITH CARE TO AVOID DAMAGE.
71. THE CONTRACTOR SHALL ENSURE ADEQUATE VENTILATION IN CABLE TUNNELS.
72. ALL CABLE SUPPORTS SHALL BE SPACED AT INTERVALS NOT EXCEEDING 1.5 METERS.
73. THE CONTRACTOR SHALL PROVIDE FIRE STOPPING AT ALL CABLE PENETRATIONS.
74. ALL CABLE GLANDS SHALL BE OF APPROVED TYPE AND SIZE.
75. THE CONTRACTOR SHALL ENSURE ADEQUATE SEPARATION BETWEEN POWER AND CONTROL CABLES.
76. ALL CABLE TERMINATIONS SHALL BE MADE IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.
77. THE CONTRACTOR SHALL PROVIDE CABLE SCHEDULES UPON COMPLETION.
78. ALL CABLE ROUTES SHALL BE APPROVED BY THE ENGINEER BEFORE INSTALLATION.
79. THE CONTRACTOR SHALL ENSURE ADEQUATE CLEARANCE FROM OTHER UTILITIES.
80. ALL CABLE TRENCHES SHALL BE MARKED WITH WARNING TAPE.
81. THE CONTRACTOR SHALL PROVIDE CABLE DRUM TURNING GEAR.
82. ALL CABLE PULLING SHALL BE DONE UNDER SUPERVISION.
83. THE CONTRACTOR SHALL ENSURE ADEQUATE LIGHTING IN CABLE TUNNELS.
84. ALL CABLE SUPPORTS SHALL BE GALVANIZED.
85. THE CONTRACTOR SHALL PROVIDE CABLE IDENTIFICATION TAGS AT ALL JUNCTIONS.
86. ALL CABLE TRENCHES SHALL BE BACKFILLED WITH APPROVED MATERIAL ONLY.
87. THE CONTRACTOR SHALL ENSURE ADEQUATE COMPACTION OF BACKFILL MATERIAL.
88. ALL CABLE JOINTS SHALL BE MADE BY CERTIFIED JOINTERS ONLY.
89. THE CONTRACTOR SHALL PROVIDE CABLE PROTECTION WHERE CABLES CROSS ROADS.
90. ALL CABLE DRUMS SHALL BE HANDLED WITH CARE TO AVOID DAMAGE.
91. THE CONTRACTOR SHALL ENSURE ADEQUATE VENTILATION IN CABLE TUNNELS.
92. ALL CABLE SUPPORTS SHALL BE SPACED AT INTERVALS NOT EXCEEDING 1.5 METERS.
93. THE CONTRACTOR SHALL PROVIDE FIRE STOPPING AT ALL CABLE PENETRATIONS.
94. ALL CABLE GLANDS SHALL BE OF APPROVED TYPE AND SIZE.
95. THE CONTRACTOR SHALL ENSURE ADEQUATE SEPARATION BETWEEN POWER AND CONTROL CABLES.
96. ALL CABLE TERMINATIONS SHALL BE MADE IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.
97. THE CONTRACTOR SHALL PROVIDE CABLE SCHEDULES UPON COMPLETION.
98. ALL CABLE ROUTES SHALL BE APPROVED BY THE ENGINEER BEFORE INSTALLATION.
99. THE CONTRACTOR SHALL ENSURE ADEQUATE CLEARANCE FROM OTHER UTILITIES.
100. ALL CABLE TRENCHES SHALL BE MARKED WITH WARNING TAPE.
101. THE CONTRACTOR SHALL PROVIDE CABLE DRUM TURNING GEAR.
102. ALL CABLE PULLING SHALL BE DONE UNDER SUPERVISION.
103. THE CONTRACTOR SHALL ENSURE ADEQUATE LIGHTING IN CABLE TUNNELS.
104. ALL CABLE SUPPORTS SHALL BE GALVANIZED.
105. THE CONTRACTOR SHALL PROVIDE CABLE IDENTIFICATION TAGS AT ALL JUNCTIONS.
106. ALL CABLE TRENCHES SHALL BE BACKFILLED WITH APPROVED MATERIAL ONLY.
107. THE CONTRACTOR SHALL ENSURE ADEQUATE COMPACTION OF BACKFILL MATERIAL.
108. ALL CABLE JOINTS SHALL BE MADE BY CERTIFIED JOINTERS ONLY.
109. THE CONTRACTOR SHALL PROVIDE CABLE PROTECTION WHERE CABLES CROSS ROADS.
110. ALL CABLE DRUMS SHALL BE HANDLED WITH CARE TO AVOID DAMAGE.
111. THE CONTRACTOR SHALL ENSURE ADEQUATE VENTILATION IN CABLE TUNNELS.
112. ALL CABLE SUPPORTS SHALL BE SPACED AT INTERVALS NOT EXCEEDING 1.5 METERS.
113. THE CONTRACTOR SHALL PROVIDE FIRE STOPPING AT ALL CABLE PENETRATIONS.
114. ALL CABLE GLANDS SHALL BE OF APPROVED TYPE AND SIZE.
115. THE CONTRACTOR SHALL ENSURE ADEQUATE SEPARATION BETWEEN POWER AND CONTROL CABLES.
116. ALL CABLE TERMINATIONS SHALL BE MADE IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.
117. THE CONTRACTOR SHALL PROVIDE CABLE SCHEDULES UPON COMPLETION.
118. ALL CABLE ROUTES SHALL BE APPROVED BY THE ENGINEER BEFORE INSTALLATION.
119. THE CONTRACTOR SHALL ENSURE ADEQUATE CLEARANCE FROM OTHER UTILITIES.
120. ALL CABLE TRENCHES SHALL BE MARKED WITH WARNING TAPE.
121. THE CONTRACTOR SHALL PROVIDE CABLE DRUM TURNING GEAR.
122. ALL CABLE PULLING SHALL BE DONE UNDER SUPERVISION.
123. THE CONTRACTOR SHALL ENSURE ADEQUATE LIGHTING IN CABLE TUNNELS.
124. ALL CABLE SUPPORTS SHALL BE GALVANIZED.
125. THE CONTRACTOR SHALL PROVIDE CABLE IDENTIFICATION TAGS AT ALL JUNCTIONS.
126. ALL CABLE TRENCHES SHALL BE BACKFILLED WITH APPROVED MATERIAL ONLY.
127. THE CONTRACTOR SHALL ENSURE ADEQUATE COMPACTION OF BACKFILL MATERIAL.
128. ALL CABLE JOINTS SHALL BE MADE BY CERTIFIED JOINTERS ONLY.
129. THE CONTRACTOR SHALL PROVIDE CABLE PROTECTION WHERE CABLES CROSS ROADS.
130. ALL CABLE DRUMS SHALL BE HANDLED WITH CARE TO AVOID DAMAGE.
131. THE CONTRACTOR SHALL ENSURE ADEQUATE VENTILATION IN CABLE TUNNELS.
132. ALL CABLE SUPPORTS SHALL BE SPACED AT INTERVALS NOT EXCEEDING 1.5 METERS.
133. THE CONTRACTOR SHALL PROVIDE FIRE STOPPING AT ALL CABLE PENETRATIONS.
134. ALL CABLE GLANDS SHALL BE OF APPROVED TYPE AND SIZE.
135. THE CONTRACTOR SHALL ENSURE ADEQUATE SEPARATION BETWEEN POWER AND CONTROL CABLES.
136. ALL CABLE TERMINATIONS SHALL BE MADE IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.
137. THE CONTRACTOR SHALL PROVIDE CABLE SCHEDULES UPON COMPLETION.
138. ALL CABLE ROUTES SHALL BE APPROVED BY THE ENGINEER BEFORE INSTALLATION.
139. THE CONTRACTOR SHALL ENSURE ADEQUATE CLEARANCE FROM OTHER UTILITIES.
140. ALL CABLE TRENCHES SHALL BE MARKED WITH WARNING TAPE.
141. THE CONTRACTOR SHALL PROVIDE CABLE DRUM TURNING GEAR.
142. ALL CABLE PULLING SHALL BE DONE UNDER SUPERVISION.
143. THE CONTRACTOR SHALL ENSURE ADEQUATE LIGHTING IN CABLE TUNNELS.
144. ALL CABLE SUPPORTS SHALL BE GALVANIZED.
145. THE CONTRACTOR SHALL PROVIDE CABLE IDENTIFICATION TAGS AT ALL JUNCTIONS.
146. ALL CABLE TRENCHES SHALL BE BACKFILLED WITH APPROVED MATERIAL ONLY.
147. THE CONTRACTOR SHALL ENSURE ADEQUATE COMPACTION OF BACKFILL MATERIAL.
148. ALL CABLE JOINTS SHALL BE MADE BY CERTIFIED JOINTERS ONLY.
149. THE CONTRACTOR SHALL PROVIDE CABLE PROTECTION WHERE CABLES CROSS ROADS.
150. ALL CABLE DRUMS SHALL BE HANDLED WITH CARE TO AVOID DAMAGE.
151. THE CONTRACTOR SHALL ENSURE ADEQUATE VENTILATION IN CABLE TUNNELS.
152. ALL CABLE SUPPORTS SHALL BE SPACED AT INTERVALS NOT EXCEEDING 1.5 METERS.
153. THE CONTRACTOR SHALL PROVIDE FIRE STOPPING AT ALL CABLE PENETRATIONS.
154. ALL CABLE GLANDS SHALL BE OF APPROVED TYPE AND SIZE.
155. THE CONTRACTOR SHALL ENSURE ADEQUATE SEPARATION BETWEEN POWER AND CONTROL CABLES.
156. ALL CABLE TERMINATIONS SHALL BE MADE IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.
157. THE CONTRACTOR SHALL PROVIDE CABLE SCHEDULES UPON COMPLETION.
158. ALL CABLE ROUTES SHALL BE APPROVED BY THE ENGINEER BEFORE INSTALLATION.
159. THE CONTRACTOR SHALL ENSURE ADEQUATE CLEARANCE FROM OTHER UTILITIES.
160. ALL CABLE TRENCHES SHALL BE MARKED WITH WARNING TAPE.
161. THE CONTRACTOR SHALL PROVIDE CABLE DRUM TURNING GEAR.
162. ALL CABLE PULLING SHALL BE DONE UNDER SUPERVISION.
163. THE CONTRACTOR SHALL ENSURE ADEQUATE LIGHTING IN CABLE TUNNELS.
164. ALL CABLE SUPPORTS SHALL BE GALVANIZED.
165. THE CONTRACTOR SHALL PROVIDE CABLE IDENTIFICATION TAGS AT ALL JUNCTIONS.
166. ALL CABLE TRENCHES SHALL BE BACKFILLED WITH APPROVED MATERIAL ONLY.
167. THE CONTRACTOR SHALL ENSURE ADEQUATE COMPACTION OF BACKFILL MATERIAL.
168. ALL CABLE JOINTS SHALL BE MADE BY CERTIFIED JOINTERS ONLY.
169. THE CONTRACTOR SHALL PROVIDE CABLE PROTECTION WHERE CABLES CROSS ROADS.
170. ALL CABLE DRUMS SHALL BE HANDLED WITH CARE TO AVOID DAMAGE.
171. THE CONTRACTOR SHALL ENSURE ADEQUATE VENTILATION IN CABLE TUNNELS.
172. ALL CABLE SUPPORTS SHALL BE SPACED AT INTERVALS NOT EXCEEDING 1.5 METERS.
173. THE CONTRACTOR SHALL PROVIDE FIRE STOPPING AT ALL CABLE PENETRATIONS.
174. ALL CABLE GLANDS SHALL BE OF APPROVED TYPE AND SIZE.
175. THE CONTRACTOR SHALL ENSURE ADEQUATE SEPARATION BETWEEN POWER AND CONTROL CABLES.
176. ALL CABLE TERMINATIONS SHALL BE MADE IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.
177. THE CONTRACTOR SHALL PROVIDE CABLE SCHEDULES UPON COMPLETION.
178. ALL CABLE ROUTES SHALL BE APPROVED BY THE ENGINEER BEFORE INSTALLATION.
179. THE CONTRACTOR SHALL ENSURE ADEQUATE CLEARANCE FROM OTHER UTILITIES.
180. ALL CABLE TRENCHES SHALL BE MARKED WITH WARNING TAPE.
181. THE CONTRACTOR SHALL PROVIDE CABLE DRUM TURNING GEAR.
182. ALL CABLE PULLING SHALL BE DONE UNDER SUPERVISION.
183. THE CONTRACTOR SHALL ENSURE ADEQUATE LIGHTING IN CABLE TUNNELS.
184. ALL CABLE SUPPORTS SHALL BE GALVANIZED.
185. THE CONTRACTOR SHALL PROVIDE CABLE IDENTIFICATION TAGS AT ALL JUNCTIONS.
186. ALL CABLE TRENCHES SHALL BE BACKFILLED WITH APPROVED MATERIAL ONLY.
187. THE CONTRACTOR SHALL ENSURE ADEQUATE COMPACTION OF BACKFILL MATERIAL.
188. ALL CABLE JOINTS SHALL BE MADE BY CERTIFIED JOINTERS ONLY.
189. THE CONTRACTOR SHALL PROVIDE CABLE PROTECTION WHERE CABLES CROSS ROADS.
190. ALL CABLE DRUMS SHALL BE HANDLED WITH CARE TO AVOID DAMAGE.
191. THE CONTRACTOR SHALL ENSURE ADEQUATE VENTILATION IN CABLE TUNNELS.
192. ALL CABLE SUPPORTS SHALL BE SPACED AT INTERVALS NOT EXCEEDING 1.5 METERS.
193. THE CONTRACTOR SHALL PROVIDE FIRE STOPPING AT ALL CABLE PENETRATIONS.
194. ALL CABLE GLANDS SHALL BE OF APPROVED TYPE AND SIZE.
195. THE CONTRACTOR SHALL ENSURE ADEQUATE SEPARATION BETWEEN POWER AND CONTROL CABLES.
196. ALL CABLE TERMINATIONS SHALL BE MADE IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.
197. THE CONTRACTOR SHALL PROVIDE CABLE SCHEDULES UPON COMPLETION.
198. ALL CABLE ROUTES SHALL BE APPROVED BY THE ENGINEER BEFORE INSTALLATION.
199. THE CONTRACTOR SHALL ENSURE ADEQUATE CLEARANCE FROM OTHER UTILITIES.
200. ALL CABLE TRENCHES SHALL BE MARKED WITH WARNING TAPE.
201. THE CONTRACTOR SHALL PROVIDE CABLE DRUM TURNING GEAR.
202. ALL CABLE PULLING SHALL BE DONE UNDER SUPERVISION.
203. THE CONTRACTOR SHALL ENSURE ADEQUATE LIGHTING IN CABLE TUNNELS.
204. ALL CABLE SUPPORTS SHALL BE GALVANIZED.
205. THE CONTRACTOR SHALL PROVIDE CABLE IDENTIFICATION TAGS AT ALL JUNCTIONS.
206. ALL CABLE TRENCHES SHALL BE BACKFILLED WITH APPROVED MATERIAL ONLY.
207. THE CONTRACTOR SHALL ENSURE ADEQUATE COMPACTION OF BACKFILL MATERIAL.
208. ALL CABLE JOINTS SHALL BE MADE BY CERTIFIED JOINTERS ONLY.
209. THE CONTRACTOR SHALL PROVIDE CABLE PROTECTION WHERE CABLES CROSS ROADS.
210. ALL CABLE DRUMS SHALL BE HANDLED WITH CARE TO AVOID DAMAGE.
211. THE CONTRACTOR SHALL ENSURE ADEQUATE VENTILATION IN CABLE TUNNELS.
212. ALL CABLE SUPPORTS SHALL BE SPACED AT INTERVALS NOT EXCEEDING 1.5 METERS.
213. THE CONTRACTOR SHALL PROVIDE FIRE STOPPING AT ALL CABLE PENETRATIONS.
214. ALL CABLE GLANDS SHALL BE OF APPROVED TYPE AND SIZE.
215. THE CONTRACTOR SHALL ENSURE ADEQUATE SEPARATION BETWEEN POWER AND CONTROL CABLES.
216. ALL CABLE TERMINATIONS SHALL BE MADE IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.
217. THE CONTRACTOR SHALL PROVIDE CABLE SCHEDULES UPON COMPLETION.
218. ALL CABLE ROUTES SHALL BE APPROVED BY THE ENGINEER BEFORE INSTALLATION.
219. THE CONTRACTOR SHALL ENSURE ADEQUATE CLEARANCE FROM OTHER UTILITIES.
220. ALL CABLE TRENCHES SHALL BE MARKED WITH WARNING TAPE.
221. THE CONTRACTOR SHALL PROVIDE CABLE DRUM TURNING GEAR.
222. ALL CABLE PULLING SHALL BE DONE UNDER SUPERVISION.
223. THE CONTRACTOR SHALL ENSURE ADEQUATE LIGHTING IN CABLE TUNNELS.
224. ALL CABLE SUPPORTS SHALL BE GALVANIZED.
225. THE CONTRACTOR SHALL PROVIDE CABLE IDENTIFICATION TAGS AT ALL JUNCTIONS.
226. ALL CABLE TRENCHES SHALL BE BACKFILLED WITH APPROVED MATERIAL ONLY.
227. THE CONTRACTOR SHALL ENSURE ADEQUATE COMPACTION OF BACKFILL MATERIAL.
228. ALL CABLE JOINTS SHALL BE MADE BY CERTIFIED JOINTERS ONLY.
229. THE CONTRACTOR SHALL PROVIDE CABLE PROTECTION WHERE CABLES CROSS ROADS.
230. ALL CABLE DRUMS SHALL BE HANDLED WITH CARE TO AVOID DAMAGE.
231. THE CONTRACTOR SHALL ENSURE ADEQUATE VENTILATION IN CABLE TUNNELS.
232. ALL CABLE SUPPORTS SHALL BE SPACED AT INTERVALS NOT EXCEEDING 1.5 METERS.
233. THE CONTRACTOR SHALL PROVIDE FIRE STOPPING AT ALL CABLE PENETRATIONS.
234. ALL CABLE GLANDS SHALL BE OF APPROVED TYPE AND SIZE.
235. THE CONTRACTOR SHALL ENSURE ADEQUATE SEPARATION BETWEEN POWER AND CONTROL CABLES.
236. ALL CABLE TERMINATIONS SHALL BE MADE IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.
237. THE CONTRACTOR SHALL PROVIDE CABLE SCHEDULES UPON COMPLETION.
238. ALL CABLE ROUTES SHALL BE APPROVED BY THE ENGINEER BEFORE INSTALLATION.
239. THE CONTRACTOR SHALL ENSURE ADEQUATE CLEARANCE FROM OTHER UTILITIES.
240. ALL CABLE TRENCHES SHALL BE MARKED WITH WARNING TAPE.
241. THE CONTRACTOR SHALL PROVIDE CABLE DRUM TURNING GEAR.
242. ALL CABLE PULLING SHALL BE DONE UNDER SUPERVISION.
243. THE CONTRACTOR SHALL ENSURE ADEQUATE LIGHTING IN CABLE TUNNELS.
244. ALL CABLE SUPPORTS SHALL BE GALVANIZED.
245. THE CONTRACTOR SHALL PROVIDE CABLE IDENTIFICATION TAGS AT ALL JUNCTIONS.
246. ALL CABLE TRENCHES SHALL BE BACKFILLED WITH APPROVED MATERIAL ONLY.
247. THE CONTRACTOR SHALL ENSURE ADEQUATE COMPACTION OF BACKFILL MATERIAL.
248. ALL CABLE JOINTS SHALL BE MADE BY CERTIFIED JOINTERS ONLY.
249. THE CONTRACTOR SHALL PROVIDE CABLE PROTECTION WHERE CABLES CROSS ROADS.
250. ALL CABLE DRUMS SHALL BE HANDLED WITH CARE TO AVOID DAMAGE.
251. THE CONTRACTOR SHALL ENSURE ADEQUATE VENTILATION IN CABLE TUNNELS.
252. ALL CABLE SUPPORTS SHALL BE SPACED AT INTERVALS NOT EXCEEDING 1.5 METERS.
253. THE CONTRACTOR SHALL PROVIDE FIRE STOPPING AT ALL CABLE PENETRATIONS.
254. ALL CABLE GLANDS SHALL BE OF APPROVED TYPE AND SIZE.
255. THE CONTRACTOR SHALL ENSURE ADEQUATE SEPARATION BETWEEN POWER AND CONTROL CABLES.
256. ALL CABLE TERMINATIONS SHALL BE MADE IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.
257. THE CONTRACTOR SHALL PROVIDE CABLE SCHEDULES UPON COMPLETION.
258. ALL CABLE ROUTES SHALL BE APPROVED BY THE ENGINEER BEFORE INSTALLATION.
259. THE CONTRACTOR SHALL ENSURE ADEQUATE CLEARANCE FROM OTHER UTILITIES.
260. ALL CABLE TRENCHES SHALL BE MARKED WITH WARNING TAPE.
261. THE CONTRACTOR SHALL PROVIDE CABLE DRUM TURNING GEAR.
262. ALL CABLE PULLING SHALL BE DONE UNDER SUPERVISION.
263. THE CONTRACTOR SHALL ENSURE ADEQUATE LIGHTING IN CABLE TUNNELS.
264. ALL CABLE SUPPORTS SHALL BE GALVANIZED.
265. THE CONTRACTOR SHALL PROVIDE CABLE IDENTIFICATION TAGS AT ALL JUNCTIONS.
266. ALL CABLE TRENCHES SHALL BE BACKFILLED WITH APPROVED MATERIAL ONLY.
267. THE CONTRACTOR SHALL ENSURE ADEQUATE COMPACTION OF BACKFILL MATERIAL.
268. ALL CABLE JOINTS SHALL BE MADE BY CERTIFIED JOINTERS ONLY.
269. THE CONTRACTOR SHALL PROVIDE CABLE PROTECTION WHERE CABLES CROSS ROADS.
270. ALL CABLE DRUMS SHALL BE HANDLED WITH CARE TO AVOID DAMAGE.
271. THE CONTRACTOR SHALL ENSURE ADEQUATE VENTILATION IN CABLE TUNNELS.
272. ALL CABLE SUPPORTS SHALL BE SPACED AT INTERVALS NOT EXCEEDING 1.5 METERS.
273. THE CONTRACTOR SHALL PROVIDE FIRE STOPPING AT ALL CABLE PENETRATIONS.
274. ALL CABLE GLANDS SHALL BE OF APPROVED TYPE AND SIZE.
275. THE CONTRACTOR SHALL ENSURE ADEQUATE SEPARATION BETWEEN POWER AND CONTROL CABLES.
276. ALL CABLE TERMINATIONS SHALL BE MADE IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.
277. THE CONTRACTOR SHALL PROVIDE CABLE SCHEDULES UPON COMPLETION.
278. ALL CABLE ROUTES SHALL BE APPROVED BY THE ENGINEER BEFORE INSTALLATION.
279. THE CONTRACTOR SHALL ENSURE ADEQUATE CLEARANCE FROM OTHER UTILITIES.
280. ALL CABLE TRENCHES SHALL BE MARKED WITH WARNING TAPE.
281. THE CONTRACTOR SHALL PROVIDE CABLE DRUM TURNING GEAR.
282. ALL CABLE PULLING SHALL BE DONE UNDER SUPERVISION.
283. THE CONTRACTOR SHALL ENSURE ADEQUATE LIGHTING IN CABLE TUNNELS.
284. ALL CABLE SUPPORTS SHALL BE GALVANIZED.
285. THE CONTRACTOR SHALL PROVIDE CABLE IDENTIFICATION TAGS AT ALL JUNCTIONS.
286. ALL CABLE TRENCHES SHALL BE BACKFILLED WITH APPROVED MATERIAL ONLY.
287. THE CONTRACTOR SHALL ENSURE ADEQUATE COMPACTION OF BACKFILL MATERIAL.
288. ALL CABLE JOINTS SHALL BE MADE BY CERTIFIED JOINTERS ONLY.
289. THE CONTRACTOR SHALL PROVIDE CABLE PROTECTION WHERE CABLES CROSS ROADS.
290. ALL CABLE DRUMS SHALL BE HANDLED WITH CARE TO AVOID DAMAGE.
291. THE CONTRACTOR SHALL ENSURE ADEQUATE VENTILATION IN CABLE TUNNELS.
292. ALL CABLE SUPPORTS SHALL BE SPACED AT INTERVALS NOT EXCEEDING 1.5 METERS.
293. THE CONTRACTOR SHALL PROVIDE FIRE STOPPING AT ALL CABLE PENETRATIONS.
294. ALL CABLE GLANDS SHALL BE OF APPROVED TYPE AND SIZE.
295. THE CONTRACTOR SHALL ENSURE ADEQUATE SEPARATION BETWEEN POWER AND CONTROL CABLES.
296. ALL CABLE TERMINATIONS SHALL BE MADE IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.
297. THE CONTRACTOR SHALL PROVIDE CABLE SCHEDULES UPON COMPLETION.
298. ALL CABLE ROUTES SHALL BE APPROVED BY THE ENGINEER BEFORE INSTALLATION.
299. THE CONTRACTOR SHALL ENSURE ADEQUATE CLEARANCE FROM OTHER UTILITIES.
300. ALL CABLE TRENCHES SHALL BE MARKED WITH WARNING TAPE.
301. THE CONTRACTOR SHALL PROVIDE CABLE DRUM TURNING GEAR.
302. ALL CABLE PULLING SHALL BE DONE UNDER SUPERVISION.
303. THE CONTRACTOR SHALL ENSURE ADEQUATE LIGHTING IN CABLE TUNNELS.
304. ALL CABLE SUPPORTS SHALL BE GALVANIZED.
305. THE CONTRACTOR SHALL PROVIDE CABLE IDENTIFICATION TAGS AT ALL JUNCTIONS.
306. ALL CABLE TRENCHES SHALL BE BACKFILLED WITH APPROVED MATERIAL ONLY.
307. THE CONTRACTOR SHALL ENSURE ADEQUATE COMPACTION OF BACKFILL MATERIAL.
308. ALL CABLE JOINTS SHALL BE MADE BY CERTIFIED JOINTERS ONLY.
309. THE CONTRACTOR SHALL PROVIDE CABLE PROTECTION WHERE CABLES CROSS ROADS.
310. ALL CABLE DRUMS SHALL BE HANDLED WITH CARE TO AVOID DAMAGE.
311. THE CONTRACTOR SHALL ENSURE ADEQUATE VENTILATION IN CABLE TUNNELS.
312. ALL CABLE SUPPORTS SHALL BE SPACED AT INTERVALS NOT EXCEEDING 1.5 METERS.
313. THE CONTRACTOR SHALL PROVIDE FIRE STOPPING AT ALL CABLE PENETRATIONS.
314. ALL CABLE GLANDS SHALL BE OF APPROVED TYPE AND SIZE.
315. THE CONTRACTOR SHALL ENSURE ADEQUATE SEPARATION BETWEEN POWER AND CONTROL CABLES.
316. ALL CABLE TERMINATIONS SHALL BE MADE IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.
317. THE CONTRACTOR SHALL PROVIDE CABLE SCHEDULES UPON COMPLETION.
318. ALL CABLE ROUTES SHALL BE APPROVED BY THE ENGINEER BEFORE INSTALLATION.
319. THE CONTRACTOR SHALL ENSURE ADEQUATE CLEARANCE FROM OTHER UTILITIES.
320. ALL CABLE TRENCHES SHALL BE MARKED WITH WARNING TAPE.
321. THE CONTRACTOR SHALL PROVIDE CABLE DRUM TURNING GEAR.
322. ALL CABLE PULLING SHALL BE DONE UNDER SUPERVISION.
323. THE CONTRACTOR SHALL ENSURE ADEQUATE LIGHTING IN CABLE TUNNELS.
324. ALL CABLE SUPPORTS SHALL BE GALVANIZED.
325. THE CONTRACTOR SHALL PROVIDE CABLE IDENTIFICATION TAGS AT ALL JUNCTIONS.
326. ALL CABLE TRENCHES SHALL BE BACKFILLED WITH APPROVED MATERIAL ONLY.
327. THE CONTRACTOR SHALL ENSURE ADEQUATE COMPACTION OF BACKFILL MATERIAL.
328. ALL CABLE JOINTS SHALL BE MADE BY CERTIFIED JOINTERS ONLY.
329. THE CONTRACTOR SHALL PROVIDE CABLE PROTECTION WHERE CABLES CROSS ROADS.
330. ALL CABLE DRUMS SHALL BE HANDLED WITH CARE TO AVOID DAMAGE.
331. THE CONTRACTOR SHALL ENSURE ADEQUATE VENTILATION IN CABLE TUNNELS.
332. ALL CABLE SUPPORTS SHALL BE SPACED AT INTERVALS NOT EXCEEDING 1.5 METERS.
333. THE CONTRACTOR SHALL PROVIDE FIRE STOPPING AT ALL CABLE PENETRATIONS.
334. ALL CABLE GLANDS SHALL BE OF APPROVED TYPE AND SIZE.
335. THE CONTRACTOR SHALL ENSURE ADEQUATE SEPARATION BETWEEN POWER AND CONTROL CABLES.
336. ALL CABLE TERMINATIONS SHALL BE MADE IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.
337. THE CONTRACTOR SHALL PROVIDE CABLE SCHEDULES UPON COMPLETION.
338. ALL CABLE ROUTES SHALL BE APPROVED BY THE ENGINEER BEFORE INST