KM 22
KM 23
KM 24
OF PRO. BENNIGANAHALLI (SUB-URBAN) STATION (LEVEL-1) (Km. 22.300)
4. OF PRO.CHANNASADRA (SUB-URBAN) STATION (ELEVATED STATION & AT GRADE PF's) Km. 24.107
UP LINE
PRO.KAGGADASAPURA ATGRADE (SUB-URBAN)
DN LINE
UIOL FOR UP LINE CH: 22068.268
UIOL FOR DN LINE CH: 22068.268
UIOL FOR UP LINE CH: 22879.148
UIOL FOR DN LINE CH: 23372.048
UIOL FOR UP LINE CH: 24412.548
UIOL FOR DN LINE CH: 24412.548
T.L.= 956.480m Loc: 22/73 CH: 22957.148m
T.L.=1084.500m Loc: 21/03 CH: 21055.668m
T.L.= 626.900m Loc: 23/25 CH: 23440.048m
T.L.=956.480m Loc: 22/01 CH: 22000.668m
T.L.=1769.880m Loc: 21/24 CH: 21447.268m
T.L.=1798.400m Loc: 25/01 CH: 25015.548m
T.L.= 1200.000m Loc: 24/21 CH: 24507.048m
T.L.= 1200.000m Loc: 24/22 CH: 24507.048m
T.L.=626.900m Loc: 22/65 CH: 22813.148m
T.L.= 1183.500m Loc: 25/37 CH: 25515.048m
T.L.=1202.700m Loc: 25/38 CH: 25515.048m
T.L.=1200.000m Loc: 23/17 CH: 23307.048m
T.L.=1200.000m Loc: 23/18 CH: 23307.048m
TENTATIVE LOCATION OF DA SHOWN. OHE TO BE SUPPORTED FROM TRUSSES AND DISTANCE OF TRUSSES REQUIRED FROM STATION BUILDING CONTRACTOR.
FP BENNIGANAHALLI CH: 23+135 KM
REFER NOTE NO. 11
SERVICE ROAD
FUTURE ROR
ACC CENTRE FOR UP MAIN
ACC CENTRE FOR DN MAIN
PRO.CURVE NO.56(UP&DN) R = 438 m, D = 4° A =14°58'19.52" TL = 57.55 m CL = 114.45 m TRL=70 SE = 120 mm V = 70 kmph
PRO.CURVE NO.57(UP&DN) R = 438 m, D = 4° A =21°054'10" TL = 81.23 m CL = 160.65 m TRL=70 SE = 120 mm V = 70 kmph
PRO.CURVE NO.58(UP) R = 900m, D = 1.94° A =4°26'56.22" TL = 34.95 m CL = 69.88 m TRL = 40 m SE = 60 mm V = 90 kmph
PRO.CURVE NO.59(UP) R =584m, D = 3.0° A =4°54'37.01" TL = 25.08 m CL = 50.049m TRL = 20 m SE = 40 mm V = 60 kmph
PRO.CURVE NO.60(UP) R = 584m, D = 3.0° A =4°34'40.37" TL = 23.38 m CL = 46.67m TRL = 20 m SE = 40 mm V = 60 kmph
PRO.CURVE NO.61(UP&DN) R = 700m, D = 2.97° A =10°26'29.19" TL = 54.298 m CL = 107.39 m TRL = 50 m SE = 80 mm V = 80 kmph
PRO.CURVE NO.54(UP&DN) R = 292 m, D = 5.99° A = 40°51'8.38" TL = 108.76 m CL = 208.23 m SE = 30 mm V = 45 kmph
PRO.CURVE NO.55(UP&DN) R = 900 m, D = 1.94° A =4°39'5.21" TL = 36.559 m CL = 73.078 m TRL=40 SE = 60 mm V = 90 kmph
PRO. TO BE DISMANTLED RUB OF SPAN 3 X 3.0 ROC BOX AT CH. 1490.30
PRO. BSRP GRADIENT
METRO RAIL LEVEL 918.099 m SUBURBAN RAIL LEVEL 906.99m GROUND LEVEL 905.826 m
CH: 22+068.268
CH: 22+495.648
CH: 22+879.148
CH:23+135.00
CH: 23+372.048
CH: 23+911.848
CH: 24+412.548


PRO. HEELALIGE
KM 22
12 PRO. BENNIGANAHALLI (SUB-URBAN) STATION (LEVEL-1)
FEED FROM BENNIGANAHALLI RSS/TSS (CORRIDOR 4)
FP BENNIGANAHALLI CH: 23+135 KM
KM 23
KM 24
13 CHANNASADRA (SUB-URBAN) STATION CH: 24+107Km
RAJANKUNTE
HORAMAVU (SUB-URBAN) STATION
PRO KAGGADASAPURA ATGRADE (SUB-URBAN)
UP LINE
DN LINE
PTFE
BM (NO)
(NC) BM
ACC UP MAIN
ACC DN MAIN
UIOL
1084.500m
956.480m
494.980m
461.500m
956.480m
626.900m
626.900m
1200.000m
604.800m
595.200m
1200.000m
1202.700m
1183.500m
610.500m
589.500m
CH: 22+068.268
CH: 22+495.648
CH: 22+879.148
CH:23+135.00
CH: 23+372.048
CH: 23+911.848
CH: 24+412.548

HORAMAVU
(SUB-URBAN) STATION

LEGEND

Sr. No.	DESCRIPTION	SYMBOL
1	OHE Span length in metres	(30)
2	Insulated Overlap (IOL)	
3	Un insulated Overlap (UIOL)	
4	Section Insulator	
5	Single Pole Isolator	
6	Double pole Isolator with Earth Heel	
7	Normal Mast with Single Cantilever Assembly at Viaduct	
8	Normal Mast with Multiple Cantilever Assembly at Viaduct	
9	Normal Mast with triple Cantilever Assembly at Viaduct	
10	Portal with Drop Arm and Single Cantilever Assembly at Viaduct	
11	Portal with Drop Arm and Double Cantilever Assembly at Viaduct	
12	Two Track Cantilever Assembly (TTC 5.50/8.0) at Viaduct	
13	Normal Mast with Single Cantilever Assembly at Grade	
14	Normal Mast with Multiple Cantilever Assembly at Grade	
15	Normal Mast with triple Cantilever Assembly at Grade	
16	Portal with Drop Arm and Single Cantilever Assembly at Grade	
17	Portal with Drop Arm and Double Cantilever Assembly at Grade	
18	Two Track Cantilever Assembly (TTC 5.50/8.0) at Grade	
19	Drop arm support with single cantilever (6"x6" DA)	
20	Drop arm support with Double cantilever (8"x6" DA)	
21	Drop arm support with triple cantilever (8"x6" DA)	
22	Anchoring stay with Fixed Termination-conv.	FTA
23	Anchoring Stay with Spring Termination Anchor	BWA
24	Versine	300
25	Anticreep Anchor	ACA
26	Anticreep Center	ACC
27	Tension Length	TL
28	Upright Details (Clearspan)	BFBU/GU(CS:xx)
29	Sub-Sectioning and Paralleling Post (SSP)	
30	Sub-Sectioning Post (SS)	
31	Sectioning and Paralleling Post (SP)	
32	Feeding Post (FP)	
33	Obligatory	OBL
34	To Be Decided	TBD
35	Interrupter(BM)	
36	Potential Transformer (PT)	
37	Lightning Arrestor (LA)	
38	Booster Transformer	
39	Spare	
40	Overhead Protection Conductor Anchor	OPCA
41	Return Conductor Anchor	RCA
42	Tramway OHE	
43	In-Run Wire	
44	Out-of Run Wire	
45	PTFE	
46	Overhead Protection Conductor	OPC
47	Return Conductor	RC
48	Cross feeder	
49	Slack feeder	
50	Full Feeding Jumper	
51	Potential Equalising Jumper	
52	In-Span Jumper	
53	RC and OPC Support	
54	Track at UP/DN line (Corridor 2)	
55	Track on Viaduct	

NOTES:-

1. ALL DIMENSIONS ARE IN METERS UNLESS NOTED OTHERWISE.
2. ALL DIMENSIONS ARE TO BE READ AND NOT TO BE MEASURED.
3. ALIGNMENT OF THE PEGGING PLAN HAS BEEN PREPARED ACCORDING TO THE ALIGNMENT DRAWING RECEIVED FROM GC / KRIDE DT. 22-06-2024.
4. OHE CHAINAGES OF THE PEGGING PLAN HAS BEEN TAKEN WITH REFERENCE TO THE OHE SPAN FROM THE PREVIOUS LOCATION.
5. SPANS ARE ROUNDED OFF TO NEAREST SINGLE DECIMAL.
6. MAST TYPE SHALL BE DEMARCATED IN PEGGING PLAN AFTER FINALIZATION OF OHE LOAD CALCULATIONS.
7. OHE HEIGHT CLEARANCE UNDER/OVER LINE STRUCTURE (HT. LINE X-ING ETC.) TO BE CONFIRMED OR SPECIAL CARE TO BE TAKEN BEFORE ERECTION FOR THAT PARTICULAR AREA WHEREVER REQUIRED.
8. OHE LOCATIONS TO BE REVISED NEAR BMRCL CROSSING B/W 22475 TO 23775 AFTER THE FINALIZATION OF PIER SPAN ARRANGEMENT AND RECEIVING OF BMRC CROSSING CROSSECTIONS FOR CLEARANCE STUDY.
9. OHE LOCATIONS IN THE ELEVATED SECTION WILL BE REEVALUATED AFTER THE FINALIZATION OF PIER SPAN ARRANGEMENT.
10. FROM LOC NO. 23/45-46 TO 24/13-12 DIFFERENT OHE CHAINAGES TO BE FOLLOWED FOR UP & DN LINE DUE TO ISLAND TYPE STATION.
11. CROSSECTION DETAILS OF BSRP RCC BOX IS REQUIRED B/W CH: 24375 - 24575 FOR FINALIZING OF OHE ARRANGEMENT.

NOTES:

1. ALL DIMENSIONS ARE IN METER UNLESS MENTIONED OTHERWISE.
2. ALL DIMENSIONS ARE TO BE READ AND NOT TO BE MEASURED.
3. ANY DISCREPANCY IN THE DRAWING MUST BE BROUGHT TO THE NOTICE OF THE DESIGNER.
4. INTERFACE WITH OTHER DESIGN DISCIPLINE WILL BE DONE AS PER AVAILABILITY OF DETAILS.

REV	DATE	DESCRIPTION	Originator	Checked	Approved
R0	30-08-2024	First Submission	KB / SB	CK/NP	RK/SK

K RIDE

DM / ELE / KRIDE	Sr. DGM / ELE / KRIDE	AGM / ELE / KRIDE

Certified that this document has been designed and checked in accordance with GC Quality Assurance Plan.

egis AECOM wsp
EGIS-AECOM-WSP

Senior Discipline Expert	Chief Discipline Expert	Project Director

Certified that this document has been designed and checked in accordance with DDC Quality Assurance Plan.
Detailed Design Consultant for design of Traction & Auxiliary Power Supply and Distribution for BSRP

SYSTRA
SYSTRA MVA CONSULTING (INDIA) PVT. LTD.
10th and 11th Floor, Tower-B, 12/3, Vatika Mindscapes, Mathura Road, NH2, Sector 27D, Faridabad, Haryana 121013

Drawn	Checked:	Approved:
K.Bisht	D. Kalyan	R. Kapoor
S. Bhati	N. Parmar	S. Kumar

FOR TENDER PURPOSE ONLY

Client:
K RIDE
RAIL INFRASTRUCTURE
DEVELOPMENT COMPANY
(KARNATAKA) LIMITED

Project Title: Bengaluru Suburban Rail Project (BSRP)
(Detailed Design Consultant for design of Traction & Auxiliary Power Supply and Distribution for BSRP)
Corridor-4 (Pro.Heelalige -Rajankunte)

Drawing Title: OHE Pegging Plan for Main Line CH: 22+000.668Km to CH: 24+725Km
Project Stage: Tender Drawing
Paper Size: 297X5000
Discipline: Power Supply & Traction System
Date: 30/08/2024
Scale: NTS
Drawing no.: KRDD01-TDR-CR04-GEN-OCS-PGP-00009
Revision: R0